



INSUL-TEC

DOUBLE HUNG

The secret behind this window's performance is its exceptionally low air infiltration ratings which can lower the energy consumption of a typical home by 25–40%. This unique feature, combined with our Heat Seal® Glass System or Heat Seal® Super Glass System, offers outstanding thermal performance and exceeds the most rigorous Energy Star Requirements.

- **Fully Welded Frame and Sash** with an exceptional thermal efficiency and outstanding strength.
- **Optional Foam-Filled Insulated Extrusions** for energy efficiency.
- **Insulated Extra-Strength Glass** increases strength and sound reduction.
- **Heat Seal® Glass System** offers thermal efficiency for fuel cost savings in any season.
- **Power Lift™ Balance System** allows smooth window operation.
- **Full Interlock with Triple Weather-Stripping** provides low air infiltration for increased comfort.
- **One Piece Sloped Sill** helps eliminate clogged and frozen weep holes as well as reducing air infiltration and chimney effect drafts.
- **Heatseal® Warm Edge Spacer System** for excellent thermal efficiency and drastic reduction in the possibility of condensation on the inside of the window.
- Available in Replacement and New Construction applications.



1. Stylish Full 3¼" Depth Welded Mainframe with a beveled colonial exterior curves that are not only beautiful, but also allow for maximum weld surface resulting in outstanding strength and years of long lasting performance.
2. The sill dam wall is mortised into the jamb adding strength and lowering the possibility of leaks that may occur at corner seals.
3. Our Insul-Tec Window offers a fully integrated lift rail giving the window a nice, contemporary look.

4. Standard Slim Profile Sash lock with tamper-proof cam ensures a much smoother turn and increases the life cycle over traditional locks .
5. Push Button Spring-Loaded Vent Latches allow both window sashes to remain partially open for ventilation.

SLIDER



- **Full 3¼" Depth Welded Mainframe** with beveled colonial exterior features curves that are not only beautiful, but also allow for maximum weld surface resulting in exceptional strength and years of long lasting performance.
- **Heat Seal® Glass System** offers thermal efficiency for fuel cost savings in any season.
- **Full Integral Interlock** with double weather-stripping.
- **The Optional Auto-Lock** features an exclusive automatic locking system which is easy to engage.
- **Heavy Gauge Fully Extruded Handles** on both sashes.
- **Fiberglass Mesh Half Screens** standard on all windows.
- Available in Replacement and New Construction applications.



1



2



3



4



5

1. OKNA Windows offers 2-lite and 3-lite (shown) sliding windows.
2. The window opens easily because it is mounted on brass wheels which allows the slider to smoothly glide across its track.
3. Push Button Spring-Loaded Vent Latches allow both window sashes to remain partially open for ventilation.

4. Standard factory bumpers are installed for a quieter operation.
5. Optional Auto-Lock features an exclusive automatic locking system which is easy to engage.

COLOR OPTIONS

OKNA Windows offers many color selections in addition to the standard Euro-White to give your home a distinct look and enhance its curb appeal. You can special order custom exterior colors from a virtually unlimited selection of paints. Our paints are environmentally safe and durable, giving your exterior a vibrant and long-lasting color finish. **All colors except Euro-White are available at an additional charge.**

INTERIOR OPTIONS



Standard Euro-White finish and
Standard Euro-White Lock



Optional Almond frame
and Optional Almond lock




Optional Cocoa frame
and Optional Cocoa lock


EXTERIOR COLORS




Euro-White



Almond



Cocoa



Bronze



Printed colors may not match the product's actual color.
Please visit a local dealer to view actual color samples.

OPTIONAL AUTO-LOCKS



White




Almond




Cocoa

GRIDS



Flat Grids
Between Glass



Contour Grids
Between Glass


Looking for a stunning design to instantly set your home apart both inside and out. A choice of decorative grids can highlight the architectural style that speaks to you. GBG (Grids Between Glass) consist of aluminum bars sealed in the insulating airspace between the two panes of glass. Because the interior and exterior glass surfaces are not affected, cleaning your windows is a much easier task. GBG grids on two tone windows are available with matching interior and exterior colors.

SCREEN

ThruVision Plus® is our fiberglass improved visibility screen. This product does for windows and doors what high-definition technology has done for television viewing: it improves the view by making it sharper and more vivid.




Industry Average Screen



ThruVision PLUS®
Standard with Insul-Tec
Windows

AIR INFILTRATION


Air Infiltration / drafts is a term used to describe the air leaking into or out of your home through the window frames. The graph shows the amount of air in cubic feet that may come through the window at speeds of 25mph.



US Department of Energy • www.energystar.gov/index.cfm?c=new_homes_features.hm_f_reduced_air_infiltration
The results are based on a tested window sample by AAMA testing window guidelines. Title of Test & Method: Air Infiltration - ASTM E 283 75 PA - (1.6 psf) 25 mph

HEAT SEAL® GLASS SYSTEM


High Performance Reflective Coatings Glass



HeatSeal™ heat reflective coatings are microscopically thin layers of metal & metal oxide that act like a filter – some energy is transmitted, some energy is reflected.

High Performance Insulated Glass Unit Spacer

Most windows are manufactured with a metal spacer in between the glass which causes excessive condensation and heat loss.



Our HeatSeal® non-metal spacer creates an excellent thermal barrier and reduces the transfer of heat and cold into the home.

Argon Gas



Filling the gap between the glass panes with a low-conductivity gas such as argon improves window performance by reducing the overall transfer of heat or cold between the inside and outside of your home.


BASIC ENERGY SAVING PACKAGE

- Heat Seal® Glass System
Double Pane Glass Unit




DELUXE ENERGY SAVING PACKAGE

- Heat Seal® Glass System
Double Pane Glass Unit
- Foam Filled Extrusions
- Locking Screen



SUPER DELUXE ENERGY SAVING PACKAGE

- Heat Seal® Super Glass System
Triple Pane Glass Unit
- Foam Filled Extrusions
- Locking Screen



SUPER DELUXE ENERGY SAVING PACKAGE with KRYPTON GAS

- Heat Seal® Super Glass System
Triple Pane Glass Unit - KRYPTON Gas
- Foam Filled Extrusions
- Locking Screen



Tomorrow's Windows ... Today



THERMAL PERFORMANCE

	Double Hung U-Value	Slider U-Value	Picture U-Value	Energy Star Minimum Northern Climate Zone
HEATSEAL GLASS PACKAGE				
Energy Saving Package	0.28	0.27	0.27	0.30
Deluxe Package	0.25	0.26	0.24	0.30
HEATSEAL SUPER GLASS PACKAGE				
Energy Saving Package	0.21	0.21	0.20	0.30
Deluxe Package	0.19	0.20	0.17	0.30
Deluxe Package - Krypton Gas	0.15	0.16	n/a	0.30

STRUCTURAL PERFORMANCE

	Double Hung (40x63)	Slider (63x44)	Picture (48x48)	Industry Minimum
DUAL GLAZED				
AAMA Rating	R 50	R 40	R 75	R15
Air Infiltration (CFM/FT ²)	0.02	0.09	< 0.01	0.3
Water Penetration (MPH)	54	59	66	33
Structural Integrity (MPH)	171	153	210	94

U-Value values may slightly change for windows made with GBG (Grids Between Glass)

WATER PENETRATION mph - Specifies wind load pressure in mph a window can withstand without leaking, under rain equivalent to 8" per hour.

STRUCTURAL INTEGRITY mph - Wind load in mph the window can withstand before breaking.

All result numbers are based on tested window sample by NFRC and AAMA testing window guidelines. Use for comparison purposes only. Actual values may vary depending on installation, size of the window, and other conditions.

All illustrations, photographs, and specifications in this publication are based on the latest product information available at the time of printing. Some windows shown with optional features. See the actual product for complete accuracy. The manufacturer reserves the right to alter or discontinue any model or specification without notice.



5601 Beaver Dam Rd.
Bristol, PA 19007
(215) 788-7000
(215) 781-1166 (fax)
www.oknawindows.com

Tomorrow's Windows ... Today

